

CHLORPLUS PROTECT™ 10

PFOA/PFOS FILTRATION



CHLORPLUS PROTECT™ 10

PFOA/PFOS FILTRATION



SPECIFICATIONS

Parts to assemble the System:

150102 housing Black/blue ¾" I/O with pressure relief
655226-43 ChlorPlus Protect 10 Cartridge

Accessories for installation:

150295 Wrench SW-2 150578 Bracket with screws

SPECIFICATIONS

- ◆ **Housing Size** 10"
- ◆ **Inlet Size** ¾" BSP
- ◆ **Housing Material** Polypropylene
- ◆ **Housing Dimensions** 130 mm x 310 mm (5.13"W x 12.45" H)
- ◆ **Cartridge Type** Carbon Block 655226-43 ChlorPlus Protect Cartridge
- ◆ **Micron Rating** 1
- ◆ **Approximate Filter Life*** 4 - 5 months
- ◆ **Capacity** 3785 Liters (1000 gallons)
- ◆ **Flow Rate** 3.78 L/min (1 gpm)
- ◆ **Feed Pressure Range** 2.06 - 8.6 bar (30 - 120 psi)
- ◆ **Temperature Range** 4.4 - 37.8°C - (40° - 100°F)
- ◆ **Replacement Cartridge** (Model/Part No.) ChlorPlus Protect 10 / 655226-43 (12/Case)

* Filter life dependent on gallon usage and overall incoming water quality.

The model ChlorPlus Protect 10, assembly of Pentair std housing 10» ¾" I/O and Chlorplus protect 10 cartridge is tested by IAPMO R&T against NSF/ANSI 53 for the reduction of perfluorooctanoic acid (PFOA) and perfluorooctane sulfonate (PFOS).

INSTALLATION TIPS

- ◆ Choose a mounting location suitable to support the full weight of the system when operating.
- ◆ Make sure to properly lubricate O-ring prior to use.
- ◆ Install vertically with bowl hanging down.
- ◆ Allow 1-½" (3.81 cm) clearance below the cartridge for easy cartridge replacement.

OPERATION TIPS

- ◆ Replace cartridge if flow rate decreases.
- ◆ Do not exceed service flow rate.
- ◆ Inspect O-ring during each cartridge change. Lubricate and/or replace if necessary.

SIZING

- ◆ Service Flow Rate: 3.78 L/min (1 gpm)

www.pentair.eu

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

MKT-TS-196-EN-A © 2024 Pentair. All rights reserved.